

# Technical data

## Flexilo and Flexilo Compact

---

---

ENGLISH



# 1 Room size

The necessary room size differs, depending on the type and size of the Flexilo storage tank. Add the following installation dimensions of the storage tank type and thus calculate the min. size of your installation room.

	<b>Flexilo Standard</b> Installation dimensions	
<b>Length / width</b>	On the filling system side: Flexilo Standard + 30cm On the sides without filling system: Flexilo Standard + 7cm	
<b>Height</b>	<b>Flexilo Standard</b> Minimum room height = 215 cm Room height for the maximum filling volume = 240 cm	
	<b>Flexilo COMPACT</b> Installation dimensions	 
<b>Length / width</b>	<b>On the side of the dispensing and filling system:</b> Flexilo Compact + 45cm <b>Filling system opposite the dispensing system:</b> Flexilo Compact + 75cm <b>On the sides with the springs:</b> Flexilo Compact + 7cm	
<b>Height</b>	<b>Flexilo COMPACT</b> Minimum room height = 185 cm Room height for the maximum filling volume = 240 cm  <b>Note:</b> Check the actual room dimensions again (particularly after plastering work) before installing the tank.	

These dimensions apply for internal filler couplings. For individual solutions with reduced space requirements, please contact your ÖkoFEN dealer.  
 The size of the different storage tank types can be found in the following table.

Storage tank type	Length	Width	Height	Filling volume with min. room height	Room height for max. filling volume
Flexilo Standard	mm	mm	mm	mm – to	mm – to
S110	1100	1100	1350	2150 – 0,45 to (Handfilling)	
S160 H	1700	1700	1970	2150 – 2,0 to	2400 – 2,5 to
S160 H 500	1700	1700	2450	2700 – 2,9 to	2900 – 3,2 to
S160 H 1000	1700	1700	2950	3200 – 3,7 to	3400 – 4,0 to
S160 H 1500	1700	1700	3450	3700 – 4,4 to	3900 – 4,7 to
S190 H	2040	2040	1970	2150 – 2,8 to	2400 – 3,2 to
S190 H 500	2040	2040	2450	2700 – 3,9 to	2900 – 4,2 to
S190 H 1000	2040	2040	2950	3200 – 5,0 to	3400 – 5,3 to
S190 H 1500	2040	2040	3450	3700 – 6,1 to	3900 – 6,4 to
S220 H	2300	2300	1970	2150 – 3,1 to	2400 – 3,6 to
S220 H 500	2300	2300	2450	2700 – 4,7 to	2900 – 5,0 to
S220 H 1000	2300	2300	2950	3200 – 6,3 to	3400 – 6,6 to
S220 H 1500	2300	2300	3450	3700 – 7,7 to	3900 – 8,0 to
S260 H	2580	2580	1970	2150 – 4,0 to	2400 – 4,6 to
S280 H 500	2900	2900	2450	2700 – 7,5 to	2900 – 7,8 to
S280 H 1000	2900	2900	2950	3200 – 9,0 to	3400 – 9,3 to
S280 H 1500	2900	2900	3450	3700 – 11,7 to	3900 – 12,0 to
S2216H	2300	1700	1970	2150 – 2,7 to	2400 – 3,1 to
S2219 H	2300	2040	1970	2150 – 3,0 to	2400 – 3,4 to
S2619 H	2580	2040	1970	2150 – 3,0 to	2400 – 3,6 to
S2622 H	2580	2300	1970	2150 – 3,6 to	2400 – 4,2 to
S2822 H 500	2900	2300	2450	2700 – 6,3 to	2900 – 6,6 to
S2822 H 1000	2900	2300	2950	3200 – 8,1 to	3400 – 8,4 to
S2822 H 1500	2900	2300	3450	3700 – 9,9 to	3900 – 10,2 to
Flexilo COMPACT	mm	mm	mm	mm – to	mm – to
KGT1814	1840	1440	1850 -1970	1850 – 1,3 to	2400 – 3,3 to
KGT1818	1840	1840	1850 -1970	1850 – 1,7 to	2400 – 4,0 to
KGT2614	2580	1440	1850 -1970	1850 – 2 to	2400 – 4,7 to
KGT2618	2580	1840	1850 -1970	1850 – 2,4 to	2400 – 6,2 to
KGT2620	2580	2040	1850 -1970	1850 – 3,3 to	2400 – 7,0 to
KGT2626	2580	2580	1850 -1970	1850 – 4 to	2400 – 8,5 to